

THE CHAMPAGNE CABINET

Manufactured in France

1-temperature cabinet

Small size



5 YEAR WARRANTY



Single-temperature cabinet, for serving or ageing champagne

Technical specifications


Equipment
Standard shelves




Fixed presentation shelf
APRESCHAMPG
8 bottles
12kg




Fixed presentation shelf
APRESMAGNUMG
5 bottles
10kg



Sliding presentation shelf
ACCHAMPG
8 bottles of champagne
6 magnum of champagne
4.8kg



Premium pack
3 sliding shelves
35 bottles or 22 magnum



(A la carte) configuration
1 fixed presentation shelf
19 bottles or 9 magnum

Capacity

35 bottles maximum or 22 magnum*

Temperature

- Default setup temperature: 5°C / 41°F
- Temperature setting range from 5°C / 41 to 12/54°F

Design

- Full Glass door
- Non reversible door (door opening side to be chosen on order)
- Removable Full glass handle
- Central lock
- Champagne coloured control panel with glossy finish
- White screen display
- LED screen with touch-sensitive keys
- 1 ambient light, amber, blue or red (colour to be selected on order)
- 3 lighting options: permanent, on door opening or off

Accessories

- 1 sliding presentation shelf, equipped with a soft close system. 8 removable bottle holders, in brushed stainless steel
- 2 fixed presentation shelves (standard or magnum bottles). 8 or 5 polished stainless steel bottle holders
- Shelves with champagne-coloured lacquer fronts
- Shiny leather finish to protect bottles and for more comfort of use
- 1 microfibre cloth
- 1 erasable felt-tip marker
- 1 EuroCave keyring

Equipment

- Charcoal filter
- Clay ball humidity cassette
- 2 adjustable feet at the front
- Condensate drip tray at the back

Regulation

- Electronic regulation
- Display of the real temperature inside the cellar
- Display of the humidity when the temperature is set between 9-12°C / 48-54°F
- Visual alarms in case of dysfunction (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)
- Automatic defrost

Technologies

- Cold production:** Air fan/Compressor R600a
- Cords:** CE/US/UK/JVAU/CH/C6
- Heat production:** Heating element
- Heatt release:** Automatic/threshold:adjustable
- Inner material:** Aluminium
- Exterior coating material:** HDF (High Density Fibreboard)
- Insulation type:** PU foam (59mm)

*Standard champagne format 75 cl- Magnum format 1.5l

General features

	Full Glass door
Gross weight packaged (kg)	60
Weight of packaging (kg)	4 (+8kg pallet)
Dimensions H x W x D (mm)	960x 680 x 720**
Dimensions in pack H x W x D	1090x 720 x 760
Color	Nero - RAL 9005

**With rear stopper without handle

Energy efficiency and consumption

Cords	230V-50Hz (R600a)	115V-60Hz (R600a)
	Type of door	Full Glass
Energy efficiency class	G	G
Annual energy consumption (kWh/year)	128	128
Sound emission (dB(A))	37	37
Sound emission class	C	C
Ambient operating temperatures (C°/°F)	0-30°C / 32-86°F	0-30°C / 32-86°F
Useful volume (litres)	205	

The champagne cabinet, in a few words...

The French way of life

The champagne cabinet is exclusively dedicated to displaying and serving champagne, it is a one-of-a-kind object. Designed to store all shapes and sizes of champagne bottles thanks to its specially designed shelves, this cabinet is a bold homage to the originality of champagne houses and their heritage.

